



# Expand Your Business Into the EV Market

## Generac EV Charger, Level 2 Plus For 40A & 48A models



### Power You Trust

- Trust Generac for superior charging power
- Charge 4X faster with Level 2, over L1
- Enjoy 20% faster charging with 48A, over 40A



### Adapt Your Business to the Future

Increase customer readiness for growing power demands and renewable energy shift



### Committed to Your Success

Gain access to comprehensive training, robust sales support, and effective marketing strategies tailored to help you succeed

General Specifications	
Model	Generac EV Charger, Level 2 Plus
Cable Length	25ft
Color	Matte Black
Charging Protocol	SAE J1772
Dimensions	7.8" x 7.9" x 3.9" (without cable)
Weight	4.4lbs (without cable)
Operating Temperature	-22°F to 104°F
Storage Temperature	-40°F to 158°F
Electrical Safety	UL 2594, UL 2231
EMC Compliance	FCC Part 15 Class B

Electrical Specifications	40A Model	48A Model
Charging Power	9.6kW	11.5kW
Rated Current	40A	48A
Connection Type	NEMA 14-50 or Hardwired	Hardwired
Rated Voltage AC ± 10%	240/208 V (Level 2), 60Hz	
Connector Type	SAE J1772 Type 1	
Configurable Current	From 6A to Rated Current	
Environmental Rating	Indoor and Outdoor Installations NEMA Type 4 per UL 50E	

User Interface and Communications	
Connectivity	Wi-Fi / Bluetooth
User Interface	Generac EV Charging App
Included Features	Smart Power Sharing

# AVAILABLE TO ORDER ON GENERAC 360