

## GB1000 and GB2000

## GB1000 and GB2000 Generac Power Station

Model G0080250 UPC: 696471091908

Model G0080260 UPC: 696471091915


### Features

- **Clean, Emission-Free, Portable Power** – Take it with you wherever you go, indoors or out.
- **Versatile Fast Recharging** – Recharge from 0-80% in 2.1 hours from a wall outlet (GB1000). Also supports input from solar, car and generator. Combine charging methods for even faster recharge times.
- **Compact, Durable Design** – Lightweight and easy to use with durable enclosure, ergonomic handle, and on-board storage.
- **Wireless Charging Pad** – 15W wireless charging for compatible devices.
- **Large Multi-Color 4.7" Display** – View charge level, remaining runtime and other key info at-a-glance.
- **Fast Solar Charging with Built-In MPPT Controller** – No controller accessory needed. Solar panels sold separately.



**AC Rated Output Running Watts 1600**  
**AC Maximum Output Starting Watts 3200**

### Control Panel



## GB1000 and GB2000

### Specifications

Product Series	GB1000 and GB2000
Model Number	G0080250 / G0080260
<b>Output</b>	
AC Rated Output Running Watts (X3)	120VAC / 13.3A (1600W / 3200W Surge)
USB-A (x2)	5VDC / 3.2A (15.5W max ea.)
USB-C (x2)	5-20VDC / 3.3A (65W max ea.)
12V Car Port	12VDC / 10A (120W max)
Wireless Charger	15W max
<b>Charge Input</b>	
AC Wall Charger	120VAC 60Hz (450W max)
DC / Solar Charger	10-28VDC 30A (468W max)
<b>Battery</b>	
Cell chemistry	Li-ion NMC
Nameplate Capacity (GB1000)	1086Wh
Nameplate Capacity (GB2000)	2106Wh
Cycle Life (GB1000)*	800 cycles to 80% capacity
Cycle Life (GB2000)*	1000 cycles to 80% capacity
Shelf Life	Charge every 3-6 months

Management System	High / Low Temp. Protection
	Overload Protection
	Over Voltage Protection
	Under Voltage Protection
	Short Circuit Protection
<b>Environmental</b>	
Discharge Temperature	-4 °F to 104 °F (-20 °C to 40 °C)
Charge Temperature	32 °F to 104 °F (0 °C to 40 °C)
Storage Temperature	
Optimal	59 °F to 77 °F (15 °C to 25 °C)
Max	-4 °F to 113 °F (-20 °C to 45 °C)
Warranty- Residential	3 Year Limited
Warranty- Commercial	1 Year Limited
Included	AC Charge Cord, Car Charger Cord, Solar Adapter Cord
*Cycle life based on charge rate of 0.5C and discharge rate of 1C at 25 °C	

### Dimensions and Weights

GB1000	
Length in (mm)	14.1 (359)
Width in (mm)	10.2 (258)
Height in (mm)	12.0 (305)
Carton Length in (mm)	16 (406)
Carton Width in (mm)	13.3 (338)
Carton Height in (mm)	15.3 (387)
Unit Weight lbs (kg)	29 (13)
Shipping Weight lbs (kg)	35 (16)

GB2000	
Length in (mm)	16.8 (425)
Width in (mm)	10.4 (265)
Height in (mm)	15.1 (384)
Carton Length in (mm)	19.6 (498)
Carton Width in (mm)	13.3 (338)
Carton Height in (mm)	20 (508)
Unit Weight lbs (kg)	43 (19.5)
Shipping Weight lbs (kg)	47.4 (21.5)

